FREE CALCULATOR

O-ring size chart: AS568 standard sizes

Every AS568 standard O-ring size with inside diameter, cross section and outside diameter in inches and millimeters, plus a finder that matches a measured O-ring to its dash number.

CHART

AS568 O-ring size chart

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-001	0.029	± .004	0.040	0.109	0.74	1.02
-002	0.042	± .004	0.050	0.142	1.07	1.27
-003	0.056	± .004	0.060	0.176	1.42	1.52
-004	0.070	± .005	0.070	0.210	1.78	1.78
-005	0.101	± .005	0.070	0.241	2.57	1.78
-006	0.114	± .005	0.070	0.254	2.90	1.78
-007	0.145	± .005	0.070	0.285	3.68	1.78
-008	0.176	± .005	0.070	0.316	4.47	1.78
-009	0.208	± .005	0.070	0.348	5.28	1.78
-010	0.239	± .005	0.070	0.379	6.07	1.78
-011	0.301	± .005	0.070	0.441	7.65	1.78
-012	0.364	± .005	0.070	0.504	9.25	1.78
-013	0.426	± .005	0.070	0.566	10.82	1.78
-014	0.489	± .005	0.070	0.629	12.42	1.78
-015	0.551	± .007	0.070	0.691	14.00	1.78

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-016	0.614	± .009	0.070	0.754	15.60	1.78
-017	0.676	± .009	0.070	0.816	17.17	1.78
-018	0.739	± .009	0.070	0.879	18.77	1.78
-019	0.801	± .009	0.070	0.941	20.35	1.78
-020	0.864	± .009	0.070	1.004	21.95	1.78
-021	0.926	± .009	0.070	1.066	23.52	1.78
-022	0.989	± .010	0.070	1.129	25.12	1.78
-023	1.051	± .010	0.070	1.191	26.70	1.78
-024	1.114	± .010	0.070	1.254	28.30	1.78
-025	1.176	± .011	0.070	1.316	29.87	1.78
-026	1.239	± .011	0.070	1.379	31.47	1.78
-027	1.301	± .011	0.070	1.441	33.05	1.78
-028	1.364	± .013	0.070	1.504	34.65	1.78
-029	1.489	± .013	0.070	1.629	37.82	1.78
-030	1.614	± .013	0.070	1.754	41.00	1.78
-031	1.739	± .015	0.070	1.879	44.17	1.78
-032	1.864	± .015	0.070	2.004	47.35	1.78
-033	1.989	± .018	0.070	2.129	50.52	1.78
-034	2.114	± .018	0.070	2.254	53.70	1.78
-035	2.239	± .018	0.070	2.379	56.87	1.78
-036	2.364	± .018	0.070	2.504	60.05	1.78
-037	2.489	± .018	0.070	2.629	63.22	1.78
-038	2.614	± .020	0.070	2.754	66.40	1.78
-039	2.739	± .020	0.070	2.879	69.57	1.78

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-040	2.864	± .020	0.070	3.004	72.75	1.78
-041	2.989	± .024	0.070	3.129	75.92	1.78
-042	3.239	± .024	0.070	3.379	82.27	1.78
-043	3.489	± .024	0.070	3.629	88.62	1.78
-044	3.739	± .027	0.070	3.879	94.97	1.78
-045	3.989	± .027	0.070	4.129	101.32	1.78
-046	4.239	± .030	0.070	4.379	107.67	1.78
-047	4.489	± .030	0.070	4.629	114.02	1.78
-048	4.739	± .030	0.070	4.879	120.37	1.78
-049	4.989	± .037	0.070	5.129	126.72	1.78
-050	5.239	± .037	0.070	5.379	133.07	1.78
-102	0.049	± .005	0.103	0.255	1.24	2.62
-103	0.081	± .005	0.103	0.287	2.06	2.62
-104	0.112	± .005	0.103	0.318	2.84	2.62
-105	0.143	± .005	0.103	0.349	3.63	2.62
-106	0.174	± .005	0.103	0.380	4.42	2.62
-107	0.206	± .005	0.103	0.412	5.23	2.62
-108	0.237	± .005	0.103	0.443	6.02	2.62
-109	0.299	± .005	0.103	0.505	7.59	2.62
-110	0.362	± .005	0.103	0.568	9.19	2.62
-111	0.424	± .005	0.103	0.630	10.77	2.62
-112	0.487	± .005	0.103	0.693	12.37	2.62
-113	0.549	± .007	0.103	0.755	13.94	2.62
-114	0.612	± .009	0.103	0.818	15.54	2.62

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-115	0.674	± .009	0.103	0.880	17.12	2.62
-116	0.737	± .009	0.103	0.943	18.72	2.62
-117	0.799	± .010	0.103	1.005	20.29	2.62
-118	0.862	± .010	0.103	1.068	21.89	2.62
-119	0.924	± .010	0.103	1.130	23.47	2.62
-120	0.987	± .010	0.103	1.193	25.07	2.62
-121	1.049	± .010	0.103	1.255	26.64	2.62
-122	1.112	± .010	0.103	1.318	28.24	2.62
-123	1.174	± .012	0.103	1.380	29.82	2.62
-124	1.237	± .012	0.103	1.443	31.42	2.62
-125	1.299	± .012	0.103	1.505	32.99	2.62
-126	1.362	± .012	0.103	1.568	34.59	2.62
-127	1.424	± .012	0.103	1.630	36.17	2.62
-128	1.487	± .012	0.103	1.693	37.77	2.62
-129	1.549	± .015	0.103	1.755	39.34	2.62
-130	1.612	± .015	0.103	1.818	40.94	2.62
-131	1.674	± .015	0.103	1.880	42.52	2.62
-132	1.737	± .015	0.103	1.943	44.12	2.62
-133	1.799	± .015	0.103	2.005	45.69	2.62
-134	1.862	± .015	0.103	2.068	47.29	2.62
-135	1.925	± .017	0.103	2.131	48.90	2.62
-136	1.987	± .017	0.103	2.193	50.47	2.62
-137	2.050	± .017	0.103	2.256	52.07	2.62
-138	2.112	± .017	0.103	2.318	53.64	2.62

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-139	2.175	± .017	0.103	2.381	55.25	2.62
-140	2.237	± .017	0.103	2.443	56.82	2.62
-141	2.300	± .020	0.103	2.506	58.42	2.62
-142	2.362	± .020	0.103	2.568	59.99	2.62
-143	2.425	± .020	0.103	2.631	61.60	2.62
-144	2.487	± .020	0.103	2.693	63.17	2.62
-145	2.550	± .020	0.103	2.756	64.77	2.62
-146	2.612	± .020	0.103	2.818	66.34	2.62
-147	2.675	± .022	0.103	2.881	67.95	2.62
-148	2.737	± .022	0.103	2.943	69.52	2.62
-149	2.800	± .022	0.103	3.006	71.12	2.62
-150	2.862	± .022	0.103	3.068	72.69	2.62
-151	2.987	± .024	0.103	3.193	75.87	2.62
-152	3.237	± .024	0.103	3.443	82.22	2.62
-153	3.487	± .024	0.103	3.693	88.57	2.62
-154	3.737	± .028	0.103	3.943	94.92	2.62
-155	3.987	± .028	0.103	4.193	101.27	2.62
-156	4.237	± .030	0.103	4.443	107.62	2.62
-157	4.487	± .030	0.103	4.693	113.97	2.62
-158	4.737	± .030	0.103	4.943	120.32	2.62
-159	4.987	± .035	0.103	5.193	126.67	2.62
-160	5.237	± .035	0.103	5.443	133.02	2.62
-161	5.487	± .035	0.103	5.693	139.37	2.62
-162	5.737	± .035	0.103	5.943	145.72	2.62

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-163	5.987	± .035	0.103	6.193	152.07	2.62
-164	6.237	± .040	0.103	6.443	158.42	2.62
-165	6.487	± .040	0.103	6.693	164.77	2.62
-166	6.737	± .040	0.103	6.943	171.12	2.62
-167	6.987	± .040	0.103	7.193	177.47	2.62
-168	7.237	± .045	0.103	7.443	183.82	2.62
-169	7.487	± .045	0.103	7.693	190.17	2.62
-170	7.737	± .045	0.103	7.943	196.52	2.62
-171	7.987	± .045	0.103	8.193	202.87	2.62
-172	8.237	± .050	0.103	8.443	209.22	2.62
-173	8.487	± .050	0.103	8.693	215.57	2.62
-174	8.737	± .050	0.103	8.943	221.92	2.62
-175	8.987	± .050	0.103	9.193	228.27	2.62
-176	9.237	± .055	0.103	9.443	234.62	2.62
-177	9.487	± .055	0.103	9.693	240.97	2.62
-178	9.737	± .055	0.103	9.943	247.32	2.62
-201	0.171	± .005	0.139	0.449	4.34	3.53
-202	0.234	± .005	0.139	0.512	5.94	3.53
-203	0.296	± .005	0.139	0.574	7.52	3.53
-204	0.359	± .005	0.139	0.637	9.12	3.53
-205	0.421	± .005	0.139	0.699	10.69	3.53
-206	0.484	± .005	0.139	0.762	12.29	3.53
-207	0.546	± .007	0.139	0.824	13.87	3.53
-208	0.609	± .009	0.139	0.887	15.47	3.53

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-209	0.671	± .009	0.139	0.949	17.04	3.53
-210	0.734	± .010	0.139	1.012	18.64	3.53
-211	0.796	± .010	0.139	1.074	20.22	3.53
-212	0.859	± .010	0.139	1.137	21.82	3.53
-213	0.921	± .010	0.139	1.199	23.39	3.53
-214	0.984	± .010	0.139	1.262	24.99	3.53
-215	1.046	± .010	0.139	1.324	26.57	3.53
-216	1.109	± .012	0.139	1.387	28.17	3.53
-217	1.171	± .012	0.139	1.449	29.74	3.53
-218	1.234	± .012	0.139	1.512	31.34	3.53
-219	1.296	± .012	0.139	1.574	32.92	3.53
-220	1.359	± .012	0.139	1.637	34.52	3.53
-221	1.421	± .012	0.139	1.699	36.09	3.53
-222	1.484	± .015	0.139	1.762	37.69	3.53
-223	1.609	± .015	0.139	1.887	40.87	3.53
-224	1.734	± .015	0.139	2.012	44.04	3.53
-225	1.859	± .018	0.139	2.137	47.22	3.53
-226	1.984	± .018	0.139	2.262	50.39	3.53
-227	2.109	± .018	0.139	2.387	53.57	3.53
-228	2.234	± .020	0.139	2.512	56.74	3.53
-229	2.359	± .020	0.139	2.637	59.92	3.53
-230	2.484	± .020	0.139	2.762	63.09	3.53
-231	2.609	± .020	0.139	2.887	66.27	3.53
-232	2.734	± .024	0.139	3.012	69.44	3.53

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-233	2.859	± .024	0.139	3.137	72.62	3.53
-234	2.984	± .024	0.139	3.262	75.79	3.53
-235	3.109	± .024	0.139	3.387	78.97	3.53
-236	3.234	± .024	0.139	3.512	82.14	3.53
-237	3.359	± .024	0.139	3.637	85.32	3.53
-238	3.484	± .024	0.139	3.762	88.49	3.53
-239	3.609	± .028	0.139	3.887	91.67	3.53
-240	3.734	± .028	0.139	4.012	94.84	3.53
-241	3.859	± .028	0.139	4.137	98.02	3.53
-242	3.984	± .028	0.139	4.262	101.19	3.53
-243	4.109	± .028	0.139	4.387	104.37	3.53
-244	4.234	± .030	0.139	4.512	107.54	3.53
-245	4.359	± .030	0.139	4.637	110.72	3.53
-246	4.484	± .030	0.139	4.762	113.89	3.53
-247	4.609	± .030	0.139	4.887	117.07	3.53
-248	4.734	± .030	0.139	5.012	120.24	3.53
-249	4.859	± .035	0.139	5.137	123.42	3.53
-250	4.984	± .035	0.139	5.262	126.59	3.53
-251	5.109	± .035	0.139	5.387	129.77	3.53
-252	5.234	± .035	0.139	5.512	132.94	3.53
-253	5.359	± .035	0.139	5.637	136.12	3.53
-254	5.484	± .035	0.139	5.762	139.29	3.53
-255	5.609	± .035	0.139	5.887	142.47	3.53
-256	5.734	± .035	0.139	6.012	145.64	3.53

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-257	5.859	± .035	0.139	6.137	148.82	3.53
-258	5.984	± .035	0.139	6.262	151.99	3.53
-259	6.234	± .040	0.139	6.512	158.34	3.53
-260	6.484	± .040	0.139	6.762	164.69	3.53
-261	6.734	± .040	0.139	7.012	171.04	3.53
-262	6.984	± .040	0.139	7.262	177.39	3.53
-263	7.234	± .045	0.139	7.512	183.74	3.53
-264	7.484	± .045	0.139	7.762	190.09	3.53
-265	7.734	± .045	0.139	8.012	196.44	3.53
-266	7.984	± .045	0.139	8.262	202.79	3.53
-267	8.234	± .050	0.139	8.512	209.14	3.53
-268	8.484	± .050	0.139	8.762	215.49	3.53
-269	8.734	± .050	0.139	9.012	221.84	3.53
-270	8.984	± .050	0.139	9.262	228.19	3.53
-271	9.234	± .055	0.139	9.512	234.54	3.53
-272	9.484	± .055	0.139	9.762	240.89	3.53
-273	9.734	± .055	0.139	10.012	247.24	3.53
-274	9.984	± .055	0.139	10.262	253.59	3.53
-275	10.484	± .055	0.139	10.762	266.29	3.53
-276	10.984	± .065	0.139	11.262	278.99	3.53
-277	11.484	± .065	0.139	11.762	291.69	3.53
-278	11.984	± .065	0.139	12.262	304.39	3.53
-279	12.984	± .065	0.139	13.262	329.79	3.53
-280	13.984	± .065	0.139	14.262	355.19	3.53

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-281	14.984	± .065	0.139	15.262	380.59	3.53
-282	15.955	± .075	0.139	16.233	405.26	3.53
-283	16.955	± .080	0.139	17.233	430.66	3.53
-284	17.955	± .085	0.139	18.233	456.06	3.53
-309	0.412	± .005	0.210	0.832	10.46	5.33
-310	0.475	± .005	0.210	0.895	12.07	5.33
-311	0.537	± .007	0.210	0.957	13.64	5.33
-312	0.600	± .009	0.210	1.020	15.24	5.33
-313	0.662	± .009	0.210	1.082	16.81	5.33
-314	0.725	± .010	0.210	1.145	18.42	5.33
-315	0.787	± .010	0.210	1.207	19.99	5.33
-316	0.850	± .010	0.210	1.270	21.59	5.33
-317	0.912	± .010	0.210	1.332	23.16	5.33
-318	0.975	± .010	0.210	1.395	24.77	5.33
-319	1.037	± .010	0.210	1.457	26.34	5.33
-320	1.100	± .012	0.210	1.520	27.94	5.33
-321	1.162	± .012	0.210	1.582	29.51	5.33
-322	1.225	± .012	0.210	1.645	31.12	5.33
-323	1.287	± .012	0.210	1.707	32.69	5.33
-324	1.350	± .012	0.210	1.770	34.29	5.33
-325	1.475	± .015	0.210	1.895	37.47	5.33
-326	1.600	± .015	0.210	2.020	40.64	5.33
-327	1.725	± .015	0.210	2.145	43.82	5.33
-328	1.850	± .015	0.210	2.270	46.99	5.33

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-329	1.975	± .018	0.210	2.395	50.17	5.33
-330	2.100	± .018	0.210	2.520	53.34	5.33
-331	2.225	± .018	0.210	2.645	56.52	5.33
-332	2.350	± .018	0.210	2.770	59.69	5.33
-333	2.475	± .020	0.210	2.895	62.87	5.33
-334	2.600	± .020	0.210	3.020	66.04	5.33
-335	2.725	± .020	0.210	3.145	69.22	5.33
-336	2.850	± .020	0.210	3.270	72.39	5.33
-337	2.975	± .024	0.210	3.395	75.57	5.33
-338	3.100	± .024	0.210	3.520	78.74	5.33
-339	3.225	± .024	0.210	3.645	81.92	5.33
-340	3.350	± .024	0.210	3.770	85.09	5.33
-341	3.475	± .024	0.210	3.895	88.27	5.33
-342	3.600	± .028	0.210	4.020	91.44	5.33
-343	3.725	± .028	0.210	4.145	94.62	5.33
-344	3.850	± .028	0.210	4.270	97.79	5.33
-345	3.975	± .028	0.210	4.395	100.97	5.33
-346	4.100	± .028	0.210	4.520	104.14	5.33
-347	4.225	± .030	0.210	4.645	107.32	5.33
-348	4.350	± .030	0.210	4.770	110.49	5.33
-349	4.475	± .030	0.210	4.895	113.67	5.33
-350	4.600	± .030	0.210	5.020	116.84	5.33
-351	4.725	± .030	0.210	5.145	120.02	5.33
-352	4.850	± .030	0.210	5.270	123.19	5.33

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-353	4.975	± .037	0.210	5.395	126.37	5.33
-354	5.100	± .037	0.210	5.520	129.54	5.33
-355	5.225	± .037	0.210	5.645	132.72	5.33
-356	5.350	± .037	0.210	5.770	135.89	5.33
-357	5.475	± .037	0.210	5.895	139.07	5.33
-358	5.600	± .037	0.210	6.020	142.24	5.33
-359	5.725	± .037	0.210	6.145	145.42	5.33
-360	5.850	± .037	0.210	6.270	148.59	5.33
-361	5.975	± .037	0.210	6.395	151.77	5.33
-362	6.225	± .040	0.210	6.645	158.12	5.33
-363	6.475	± .040	0.210	6.895	164.47	5.33
-364	6.725	± .040	0.210	7.145	170.82	5.33
-365	6.975	± .040	0.210	7.395	177.17	5.33
-366	7.225	± .045	0.210	7.645	183.52	5.33
-367	7.475	± .045	0.210	7.895	189.87	5.33
-368	7.725	± .045	0.210	8.145	196.22	5.33
-369	7.975	± .045	0.210	8.395	202.57	5.33
-370	8.225	± .050	0.210	8.645	208.92	5.33
-371	8.475	± .050	0.210	8.895	215.27	5.33
-372	8.725	± .050	0.210	9.145	221.62	5.33
-373	8.975	± .050	0.210	9.395	227.97	5.33
-374	9.225	± .055	0.210	9.645	234.32	5.33
-375	9.475	± .055	0.210	9.895	240.67	5.33
-376	9.725	± .055	0.210	10.145	247.02	5.33

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-377	9.975	± .055	0.210	10.395	253.37	5.33
-378	10.475	± .060	0.210	10.895	266.07	5.33
-379	10.975	± .060	0.210	11.395	278.77	5.33
-380	11.475	± .065	0.210	11.895	291.47	5.33
-381	11.975	± .065	0.210	12.395	304.17	5.33
-382	12.975	± .065	0.210	13.395	329.57	5.33
-383	13.975	± .070	0.210	14.395	354.97	5.33
-384	14.975	± .070	0.210	15.395	380.37	5.33
-385	15.955	± .075	0.210	16.375	405.26	5.33
-386	16.955	± .080	0.210	17.375	430.66	5.33
-387	17.955	± .085	0.210	18.375	456.06	5.33
-388	18.955	± .090	0.210	19.375	481.46	5.33
-389	19.955	± .095	0.210	20.375	506.86	5.33
-390	20.955	± .095	0.210	21.375	532.26	5.33
-391	21.955	± .095	0.210	22.375	557.66	5.33
-392	22.940	± .105	0.210	23.360	582.68	5.33
-393	23.940	± .110	0.210	24.360	608.08	5.33
-394	24.940	± .115	0.210	25.360	633.48	5.33
-395	25.940	± .120	0.210	26.360	658.88	5.33
-400	1.350	± .012	0.275	1.900	34.29	6.99
-401	1.475	± .015	0.275	2.025	37.47	6.99
-402	1.600	± .015	0.275	2.150	40.64	6.99
-403	1.725	± .015	0.275	2.275	43.82	6.99
-404	1.850	± .015	0.275	2.400	46.99	6.99

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-405	1.975	± .018	0.275	2.525	50.17	6.99
-406	2.100	± .018	0.275	2.650	53.34	6.99
-407	2.225	± .018	0.275	2.775	56.52	6.99
-408	2.350	± .018	0.275	2.900	59.69	6.99
-409	2.475	± .020	0.275	3.025	62.87	6.99
-410	2.600	± .020	0.275	3.150	66.04	6.99
-411	2.725	± .020	0.275	3.275	69.22	6.99
-412	2.850	± .020	0.275	3.400	72.39	6.99
-413	2.975	± .024	0.275	3.525	75.57	6.99
-414	3.100	± .024	0.275	3.650	78.74	6.99
-415	3.225	± .024	0.275	3.775	81.92	6.99
-416	3.350	± .024	0.275	3.900	85.09	6.99
-417	3.475	± .024	0.275	4.025	88.27	6.99
-418	3.600	± .028	0.275	4.150	91.44	6.99
-419	3.725	± .028	0.275	4.275	94.62	6.99
-420	3.850	± .028	0.275	4.400	97.79	6.99
-421	3.975	± .028	0.275	4.525	100.97	6.99
-422	4.100	± .028	0.275	4.650	104.14	6.99
-423	4.225	± .030	0.275	4.775	107.32	6.99
-424	4.350	± .030	0.275	4.900	110.49	6.99
-425	4.475	± .033	0.275	5.025	113.67	6.99
-426	4.600	± .033	0.275	5.150	116.84	6.99
-427	4.725	± .033	0.275	5.275	120.02	6.99
-428	4.850	± .033	0.275	5.400	123.19	6.99

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-429	4.975	± .037	0.275	5.525	126.37	6.99
-430	5.100	± .037	0.275	5.650	129.54	6.99
-431	5.225	± .037	0.275	5.775	132.72	6.99
-432	5.350	± .037	0.275	5.900	135.89	6.99
-433	5.475	± .037	0.275	6.025	139.07	6.99
-434	5.600	± .037	0.275	6.150	142.24	6.99
-435	5.725	± .037	0.275	6.275	145.42	6.99
-436	5.850	± .037	0.275	6.400	148.59	6.99
-437	5.975	± .037	0.275	6.525	151.77	6.99
-438	6.225	± .040	0.275	6.775	158.12	6.99
-439	6.475	± .040	0.275	7.025	164.47	6.99
-440	6.725	± .040	0.275	7.275	170.82	6.99
-441	6.975	± .040	0.275	7.525	177.17	6.99
-442	7.225	± .045	0.275	7.775	183.52	6.99
-443	7.475	± .045	0.275	8.025	189.87	6.99
-444	7.725	± .045	0.275	8.275	196.22	6.99
-445	7.975	± .045	0.275	8.525	202.57	6.99
-446	8.475	± .055	0.275	9.025	215.27	6.99
-447	8.975	± .055	0.275	9.525	227.97	6.99
-448	9.475	± .055	0.275	10.025	240.67	6.99
-449	9.975	± .055	0.275	10.525	253.37	6.99
-450	10.475	± .060	0.275	11.025	266.07	6.99
-451	10.975	± .060	0.275	11.525	278.77	6.99
-452	11.475	± .060	0.275	12.025	291.47	6.99

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-453	11.975	± .060	0.275	12.525	304.17	6.99
-454	12.475	± .060	0.275	13.025	316.87	6.99
-455	12.975	± .060	0.275	13.525	329.57	6.99
-456	13.475	± .070	0.275	14.025	342.27	6.99
-457	13.975	± .070	0.275	14.525	354.97	6.99
-458	14.475	± .070	0.275	15.025	367.67	6.99
-459	14.975	± .070	0.275	15.525	380.37	6.99
-460	15.475	± .070	0.275	16.025	393.07	6.99
-461	15.955	± .075	0.275	16.505	405.26	6.99
-462	16.455	± .075	0.275	17.005	417.96	6.99
-463	16.955	± .080	0.275	17.505	430.66	6.99
-464	17.455	± .085	0.275	18.005	443.36	6.99
-465	17.955	± .085	0.275	18.505	456.06	6.99
-466	18.455	± .085	0.275	19.005	468.76	6.99
-467	18.955	± .090	0.275	19.505	481.46	6.99
-468	19.455	± .090	0.275	20.005	494.16	6.99
-469	19.955	± .095	0.275	20.505	506.86	6.99
-470	20.955	± .095	0.275	21.505	532.26	6.99
-471	21.955	± .100	0.275	22.505	557.66	6.99
-472	22.940	± .105	0.275	23.490	582.68	6.99
-473	23.940	± .110	0.275	24.490	608.08	6.99
-474	24.940	± .115	0.275	25.490	633.48	6.99
-475	25.940	± .120	0.275	26.490	658.88	6.99
-901	0.185	± .005	0.056	0.297	4.70	1.42

AS568 DASH	ID (IN)	ID TOLERANCE (IN)	CROSS SECTION (IN)	OD (IN)	ID (MM)	CROSS SECTI
-902	0.239	± .005	0.064	0.367	6.07	1.63
-903	0.301	± .005	0.064	0.429	7.65	1.63
-904	0.351	± .005	0.072	0.495	8.92	1.83
-905	0.414	± .005	0.072	0.558	10.52	1.83
-906	0.468	± .005	0.078	0.624	11.89	1.98
-907	0.530	± .007	0.082	0.694	13.46	2.08
-908	0.644	± .009	0.087	0.818	16.36	2.21
-909	0.706	± .009	0.097	0.900	17.93	2.46
-910	0.755	± .009	0.097	0.949	19.18	2.46
-911	0.863	± .009	0.116	1.095	21.92	2.95
-912	0.924	± .009	0.116	1.156	23.47	2.95
-913	0.986	± .010	0.116	1.218	25.04	2.95
-914	1.047	± .010	0.116	1.279	26.59	2.95
-916	1.171	± .010	0.116	1.403	29.74	2.95
-918	1.355	± .012	0.116	1.587	34.42	2.95
-920	1.475	± .014	0.118	1.711	37.47	3.00
-924	1.720	± .014	0.118	1.956	43.69	3.00
-928	2.090	± .018	0.118	2.326	53.09	3.00
-932	2.337	± .018	0.118	2.573	59.36	3.00

Free chart from fleetzap.com/tools/o-ring-size-chart